



	Flange width (mm): F2 (right)	3.2	3.2	3.2	3.2	3.2	3.2	2.3
G	Chain line (mm): G1 (outward assembly)	46.8	46.8	47.7	47.85	46.8	45.3	46.5
	Chain line (mm): G2 (inward assembly)	41.8	41.8	42.7	42.85	41.8	40.3	41.5
H	Dishing distance (mm)	3.15	3.15	2.7	2.55	4	3.85	4.6
J	Axle length from hub (left)	26	26	26	25.7	26.6	26 or 37	24.5
K	Axle length from hub (right)	26	26	26	26	25.4	26 or 34	24
L	Axle size	BC3 / 8 TPI 26						
N	Dropout width (left, includes stay etc.)	5-9	5-9	4-9	4-9	4-9	4-9 or 15 - 20	4-9
P	Dropout width (right, includes stay etc.)	5-9	5-9	4-9	4-9	4-9	4-9 or 12-17	4-9
Q	Non-turn washer width	6.4	6.4	6.4	6.4	6.4	6.4	6.4
R	Spoke hole diameter (mm)	2.9	2.9	2.9	2.9	2.9	2.9	2.7
S	Spoke hole chamfer	90°	90°	90°	90°	90°	90°	105°

## Still Need Help?

You can [schedule a service appointment](#), [send us an email](#), or give us a call at 415-524-7362. We're here to help!